



Applications

BCI Group Size Conversion

BCI Group Size	ODYSSEY Battery Model	CCA 30 sec at 0° F	CA 30 sec at 32°F	HCA 30 sec at 80°F	5 second Cranking 80°F	Reserve Minutes 80°F	Usable Reserve Minutes	Max. Overall Dimen.		
								L	W	H
PASSENGER CAR AND LIGHT COMMERCIAL BATTERIES 12-VOLT										
21		310-400	385-500	450-580	540-695	50-70	15-21	8 3/16	6 13/16	8 3/4
	PC680MJT *1	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
	PC925MJT *2	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
21R		310-500	385-625	450-725	540-870	50-70	15-21	8 3/16	6 13/16	8 3/4
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
22F		220-425	275-530	320-615	380-735	45-90	14-27	9 1/2	6 7/8	8 5/16
22NF		210-325	260-405	300-470	360-560	50-60	15-18	9 7/16	5 1/2	8 15/16
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
24		350-625	435-780	505-905	605-1085	70-95	21-29	10 1/4	6 13/16	8 7/8
25		310-490	385-610	450-710	540-850	50-90	15-27	9 1/16	6 7/8	8 7/8
26		310-440	385-550	450-635	540-760	50-80	15-24	8 13/16	6 13/16	7 3/4
	PC680MJT *1	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
	PC925MJT *2	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
	PC1200MJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16
24F		350-585	435-730	505-845	605-1010	70-95	21-29	10 3/4	6 13/16	9
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	6 9/16
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
26R		405-525	505-655	585-760	700-910	60-80	18-24	8 13/16	6 13/16	7 3/4
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
27		360-700	450-875	520-1015	620-1215	102-140	31-42	12 1/16	6 13/16	8 7/8
	PC1200LMJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16

27F		360-660	450-825	520-955	620-1145	95-140	29-42	12 1/2	6 13/16	8 15/16	
	PC1200MJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
29NF		330-350	410-435	475-505	570-605	95	29	13	5 1/2	8 15/16	
	PC925MJT *4	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
34		375-650	465-810	540-940	645-1125	100-110	30-33	10 1/4	6 13/16	7 7/8	
	PC1200LMJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
34R		675	840	975	1170	110	33	10 1/4	6 13/16	7 7/8	
35		310-500	385-625	450-725	540-870	80-110	24-33	9 1/16	6 7/8	8 7/8	
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
	PC1200MJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
41		235-650	290-810	340-940	405-1125	65-95	19-28	11 9/16	6 7/8	6 7/8	
42		260-495	325-615	375-715	450-855	65-95	19-28	9 9/16	6 13/16	6 13/16	
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
45		250-470	310-585	360-680	430-815	60-80	18-24	9 7/16	5 1/2	8 15/16	
	PC680MJT *1	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16	
	NOTES:										
	*1 Installation requires reverse mounting orientation for correct terminal polarity										
	*2 Installation requires battery side mount for correct terminal polarity										
	*4 Installation requires battery to be placed on its side to dimensionally fit										
	ODYSSEY Batteries are universal in fit and may require non-OEM hold down brackets or spacers										
BCI Group Size	ODYSSEY Battery Model	CCA 30 sec at 0° F	CA 30 sec at 32°F	HCA 30 sec at 80°F	5 second Cranking 80°F	Reserve Minutes 80°F	Usable Reserve Minutes	Max. Overall Dimen.			
								L	W	H	
PASSENGER CAR AND LIGHT COMMERCIAL BATTERIES 12-VOLT											
46		350-450	435-560	505-650	605-780	75-95	22-28	10 3/4	6 13/16	9	
	PC1200LMJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
47		370-550	460-685	535-795	640-950	75-85	22-25	9 11/16	6 7/8	7 1/2	
48		450-695	560-865	650-1005	780-1205	85-95	25-28	12 1/16	6 7/8	7 9/16	
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
	PC1200MJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
49		600-810	750-1010	870-1170	1040-1400	140-150	42-45	15	6 7/8	7 9/16	
	PC1200MJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
50		400-600	500-750	580-870	695-1040	85-100	25-30	13 1/2	5	10	
	PC925MJT *4	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	

51		405-435	505-540	585-630	700-755	70	21	9 3/8	5 1/16	8 13/16	
	PC680MJT *1	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16	
51R		405-435	505-540	585-630	700-755	70	21	9 3/8	5 1/16	8 13/16	
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16	
53		280	350	405	485	40	12	13	4 11/16	8 1/4	
	PC680MJT *1	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16	
54		305-330	380-410	440-475	525-570	60	18	7 5/16	6 1/16	8 3/8	
55		370-450	460-560	535-650	640-780	75	22	8 5/8	6 1/16	8 3/8	
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16	
56		450-505	560-630	650-730	780-875	90	27	10	6 1/16	8 3/8	
	PC N/A										
58		380-540	475-675	550-780	660-935	75	22	10 1/16	7 3/16	6 15/16	
	PC925MJT *2	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
58R		540	675	780	935	75	22	10 1/16	7 3/16	6 15/16	
	PC925MJT	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
62		380	475	550	660	75	22	8 7/8	6 3/8	8 7/8	
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16	
64		475-535	590-665	685-775	665-750	105-120	31-36	11 11/16	6 3/8	8 7/8	
	PC925MJT *4	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16	
65		650-850	810-1060	940-1230	1090-1475	130-165	39-50	12 1/16	7 1/2	7 9/16	
	PC1200LMJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16	
	NOTES:										
	*1 Installation requires reverse mounting orientation for correct terminal polarity										
	*2 Installation requires battery side mount for correct terminal polarity										
	*4 Installation requires battery to be placed on its side to dimensionally fit										
	ODYSSEY Batteries are universal in fit and may require non-OEM hold down brackets or spacers										
BCI	ODYSSEY	CCA	CA	HCA	5 second	Reserve	Usable	Max.	Overall	Dimen.	

Group	Battery	30 sec at	30 sec at	30 sec at	Cranking	Minutes	Reserve			
Size	Model	0 F	32 F	80 F	80 F	80 F	Minutes	L	W	H
		PASSENGER CAR AND LIGHT COMMERCIAL BATTERIES 12-VOLT								
74		350-550	435-685	505-795	605-950	75-140	23-42	10 1/4	7 1/4	8 3/4
75		430-690	535-860	620-1000	740-1200	90	27	9 1/16	7 1/16	7 11/16
	PC925MJT *2	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
	PC1200MJT *2	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16
78		515-770	640-960	745-1115	890-1335	105-115	31-34	10 1/4	7 1/16	7 11/16
	PC1200MJT *2	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16
86		430-525	535-655	620-760	740-910	90	27	9 1/16	6 13/16	8
	PC925MJT *2	360	455	540	925	53	37	6 9/16	6 7/8	6 5/16
91		600	750	870	1045	100	30	11	6 7/8	6 7/8
	PC N/A									
93		800	1000	1160	1390	150	45	15	6 7/8	6 7/8
	(2P) PC925MJT *3	720	910	1080	1850	106	63	13 1/8	6 7/8	6 5/16
		GARDEN TRACTOR - UTILITY BATTERIES 12-VOLT								
U1		120-295	150-365	170-425	200-510	23-40	7-12	7 3/4	5 3/16	7 5/16
	PC680MJT *1	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
U1R		220-235	275-290	315-340	375-405	25-37	7-11	7 3/4	5 3/16	7 5/16
	PC680MJT	210	270	330	680	28	19	7 3/16	3 1/16	7 3/16
		HEAVY-DUTY COMMERCIAL BATTERIES 12-VOLT								
6 TL		600	750	870	1040	200	60	11 1/4	10 1/2	9 9/16
	PC1200MJT	530	675	790	1200	91	63	7 13/16	6 9/16	8 1/16
8D		850-1250	1060-1560	1230-1810	1475-2170	235-465	70-140	20 3/4	11 1/8	9 7/8
	(2P) PC1200MJT *3	1060	1350	1580	2400	182	127	15 5/8	6 9/16	8 1/16

	(3P) PC1200MJT *3	1590	2025	2370	3600	273	191	19 9/16	7 13/16	8 1/16	
	PC1700MJT	840	1055	1225	1700	156	109	13 6 5/8	7 5/8		
29H/30H		525-840	655-1050	760-1215	910-1455	145	43	13 1/8	6 3/4	9 1/8	
	PC1700MJT	840	1055	1225	1700	156	109	13 6 5/8	7 5/8		
31		455-950	565-1185	660-1375	790-1650	100-200	30-60	13	6 13/16	9 7/16	
	(2P) PC925MJT *3	720	910	1080	1850	106	63	13 1/8	6 7/8	6 5/16	
	PC1700MJT	840	1055	1225	1700	156	109	13 6 5/8	7 5/8		
		HEAVY-DUTY MOTOR COACH AND BUS BATTERIES 12-VOLT									
4D		490-950	610-1185	710-1375	850-1650	225-325	67-97	20 3/4	8 3/4	9 7/8	
	(2P) PC1200MJT	1060	1350	1580	2400	182	127	15 5/8	6 9/16	8 1/16	
	PC1700MJT	840	1055	1225	1700	156	109	13 6 5/8	7 5/8		
		SPECIAL TRACTOR BATTERIES 12-VOLT									
3EE		260-360	325-450	375-520	450-620	80-105	24-31	19 5/16	4 3/8	8 7/8	
3ET		355-425	440-530	510-615	610-735	130-135	39-40	19 5/16	4 3/8	9 13/16	
	(2P) PC680MJT *3	420	540	660	1360	56	39	14 3/8	3 1/16	7 3/16	
4DLT		650-820	810-1025	940-1185	1125-1420	200-290	60-87	20	8 3/16	7 15/16	
	PC1700MJT	840	1055	1225	1700	156	109	13 6 5/8	7 5/8		
12T		460	575	665	795	160	48	7 1/16	6 15/16	7 15/16	
	(2P) PC680MJT *3	420	540	660	1360	56	39	7 3/16	6 1/8	7 3/16	
16TF		600	750	870	1040	240	72	16 9/16	7 1/8	11 1/8	
17TF		510	635	735	880	145	43	17 1/16	6 15/16	7 15/16	
	PC1700MJT	840	1055	1225	1700	156	109	13 6 5/8	7 5/8		
	NOTES:	*1 Installation requires reverse mounting orientation for correct terminal polarity									
		*2 Installation requires battery side mount for correct terminal polarity									
		*3 Installation requires additional interbattery cables for parallel connections									

		ODYSSEY Batteries are universal in fit and may require non-OEM hold down brackets or spacers							

© Copyright 2005 EnerSys - All rights reserved.