

Data Sheet Model No.: VCL001

Document Number: SDS0325 Revision: 05 Page 1 of 3

Specifications:

Model No : VCL001

For use with : Canon Camcorder (MV series, UCV series, UCX series, XL1, MX1)

 $\begin{array}{lll} \mbox{Color} & : & \mbox{Black (BLK)} \\ \mbox{Battery Type} & : & \mbox{Lithium Ion} \\ \mbox{Battery} & : & 2 \times 1865 \mbox{L}180 \\ \end{array}$

Nominal Voltage : 7.4V Maximum Charge Voltage : 8.4V Discharge Cut Off Voltage : 5.6V

Nominal Capacity : 1800 mAh at 0.2C**

Minimum Capacity : 1750 mAh at 0.2C**

Capacitan Capacitan Time* : 120 min (CR)

Continuous Operating Time* : 130 mins (SP)
Temperature Range : Charge: 0 ~ 45° C

Discharge: $-15 \sim 55^{\circ}$ C Storage: $-20 \sim 55^{\circ}$ C

Casing Material : ABS + PC Typical Weight : 94.3g

Safety : Each battery pack is a protection circuit that would protect

against over-voltage, over-discharge and over-current abuses occur. Every Lithium Ion cell is provided with several internal safety features to prevent over-charge, over-current, and to resist physical abuse. Each has a temperature sensitive shut down separator, pressure sensitive tear away tab for current interruption, a safety vent, and the industries only

temperature actuated current interrupter.

Warranty : Six (6) months limited warranty from date of purchase.

(Detail refer to Lithium-Ion Battery Product Specification.)

Brand names of camcorders are registered trademarks of the respective manufacturers.

^{&#}x27;*' data valid only when the battery pack is on fully charged condition.


^{&#}x27;**' Battery pack should be firstly charged and discharged for 3 complete cycles as a warm-up.



Data Sheet Model No.: VCL001

Document Number: SDS0325 Revision: 05 Page 2 of 3

Mechanical Drawing:




Remark: Dimensions showed are for reference only. For detail, please refer to the engineering drawing.



Data Sheet Model No.: VCL001

Document Number: SDS0325 Revision: 05 Page 3 of 3

Circuit Diagram:



□CV A-	-B 7.4∨ MIN	. (A IS	+VE	TERMINAL)
CHECK POIN	T SPECIFIC	ATION		

Distributed by:

MICROBATTERY.COM

7350 NW 35th Terrace, Miami, Florida 33122

Customer Service: 1-866-999-2355 Phone: 1-305-371-9200 Fax: 1-305-371-9400

www.microbattery.com

