


コイン形二酸化マンガンリチウム電池
Coin manganese dioxide lithium batteries

CR1620


■外形寸法 Dimensions



(Unit : mm)


■定格 Specifications

公称電圧 Nominal Voltage	3.0 V
公称容量 (終止電圧2.0V) Nominal Capacity (2.0V cutoff)	80 mAh
標準放電電流値 Standard Discharge Current	0.1 mA
標準質量 Weight	1.3 g
使用温度範囲 Operating Temperature	-30 ~ +70°C
UL認定合格部品 UL Recognized components ● 許可番号 Certification number : MH12566 ● User replaceable	




■ 放電負荷特性

Discharge Characteristics on Load
Test Condition: constant discharge




■ 放電温度特性

Discharge Characteristics on Temperature
Test Condition: constant discharge




■ 放電負荷と作動電圧 (放電深度40%時の電圧)
Discharge Load vs. Operation Voltage
(Discharge depth 40%)




■ 放電負荷と電気容量

Discharge Load vs. Discharge Capacity




■ パルス放電特性 (放電深度40%時のパルス電圧)
Discharge Characteristics on Pulse Load
(Discharge depth 40%)



■ 保存特性

Storage Characteristics
Test Condition: constant discharge



*記載のデータ及び数値は、参考値であり保証値ではありません。
*Data is not guaranteed, and is provided for reference purposes only.