MICROBATTERY.COM

7350 NW 35th Terrace, Miami, Florida 33122 Customer Service: 1-866-999-2355 Phone: 1-305-371-9200 Fax: 1-305-371-9400

www.microbattery.com

ENERGIZER A544


ZEROMERCURY

Miniature Alkaline



Industry Standard Dimensions

mm (inches)



Designed specifically for photo use

Specifications

Chemical System: Manganese Dioxide (MnO₂)

ANSI/NEDA-1414A, IEC-4LR44 Designation:

6.0 volts Nominal Voltage:

Typical Weight: 9.8 grams (0.3 oz)

3.3 cubic centimeters (0.2 cubic inch) Typical Volume:

Typical Capacity: 152 mAh to 3.6 volts

(rated at 27k ohms at 21°C)

Cells: Four No. LR44 in series


Metal Jacket:

Typical Discharge Characteristics

21°C (70°F)

			Cutoff Voltage
Schedule (time)	Drain (mA)	Load (ohms)	3.6V (hours)
Continuous	0.187	27K	800

Discharge Characteristics



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication. ©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Form No. EBC - 4409I-Z Page 1 of 1